

DEVICE AND METHOD FOR PRODUCING CONTAINER BLANKSField of the Invention

The present invention relates to a device and a method for producing container blanks and, more specifically, such a method and device where opposite wall portions of a material web are joined along connecting portions.

Background Art

WO99/41155 discloses a device for making container blanks by joining opposite wall portions of a material web along connecting portions.

The material web comprises two side wall webs which are passed in a parallel opposite relationship along a manufacturing line and, between them, a bottom wall web folded in two. The webs are thus brought together to a common material web and sealed to each other along said connecting portions by means of heating jaws which engage the material web.

While the heating jaws engage the material web, the web must be kept stationary, which means that the method for producing the container blanks will be intermittent.

The intermittent method of production affects the production capacity which in some cases can be insufficient.

Different solutions for increasing the production capacity have been suggested.

For example, a shaped roller forming a nip together with a back-pressure roller can be used. The material web is passed through the nip, and the shaped roller engages to form said connecting portions. The method allows continuous production of container blanks.

For the container blanks to form liquid-tight containers in the filled state, it is important for the connecting portions to be reliable, i.e. that the sealing

Summary of the Invention

A further object is to provide such a device and method which allow continuous production of container blanks of said type.

It is also an object of the invention that the device and the method allow production of container blanks with reliable connecting portions.

More specifically, there is provided according to the present invention a device for producing container blanks from a material web, comprising a plurality of tools supported by a rotary tool holder, which on rotation is arranged to move each tool along a working path along which each tool is engageable with the material web

for joining of opposite wall portions of the material web along connecting portions, and a return path along which each tool is disengageable from the material web, each tool being arranged to be moved together with the material web when the tool is moved along said working path, and said tool holder acting as a deflecting means for the material web when this moves together with the respective tools along said working path.

This results in an alternative device for producing container blanks.

The inventive device allows continuous production of container blanks since the tools during their engaging phase are moved together with the material web along said working path. However, it will be appreciated that the device can also be driven intermittently, for instance, by indexing the motion of the tool holder.

The inventive device can also be made to exhibit an advantageously high production capacity. The reason for this is that the tools are moved by rotation of the tool holder, and by arranging the tools at a suitable radial distance from the centre of rotation of the tool holder, the speed at which the tools are moved can, at a given speed of rotation, be adjusted to the desired feed rate of the material web.

The device also allows production of container blanks with reliable connecting portions to provide liquid-tight container blanks. The reliability of the connecting portions is a function of the required sealing time, by which is meant the period of time during which each tool must engage the material web for a reliable sealing portion to be formed. The inventive device can provide the required sealing time since the tool holder acts as a deflecting means for the material web when this is moved together with the tools along the working path. The tools are moved by rotation of the tool holder, thereby making it possible to provide the required sealing time for a given sealing temperature by

suitable adjustment of the speed at which the tool is moved and the distance along which the tool is moved. Said speed is a function of the speed of rotation of the tool holder and the radial distance of the tool from said
5 centre of rotation, while said distance is a function of said radial distance and the extent of the working path.

According to an embodiment of the inventive device, each tool is operable between a closed position and an open position, the tool being moved to said closed position to provide said engagement with the material web.
10 Each tool may comprise a base element which is fixedly mounted on the tool holder and an engaging element which is pivotable relative to the base element. One of the base element and the engaging element of each tool can
15 support a rib, which is arranged to engage the material web in the closed position of the tool, in which case said rib of each tool can have an extent that corresponds to the extent of the connecting portion of a container blank.

20 The rib can be supported by an arrangement involving springs, which when moving the tool to said closed position are arranged for a given compression. By a suitable adaptation of said springs, the force by which the tool is closed can thus be adjusted.

25 According to another embodiment, each tool is arranged to provide said joining by heat sealing.

According to yet another embodiment, the device comprises a control means which is arranged to engage said tool with, and disengage the same from, the material web.
30 The control means may comprise a link mechanism for each of the tools and a stationary cam structure, each tool being connected to the cam structure by said link mechanism and the cam structure being arranged, during rotation of the tool holder, to control each tool to be closed and opened, respectively. By using a single cam structure for operating all tools, the individual tools are
35 controlled in a simple and cost-effective manner. Each

link mechanism may comprise an articulated link arm which is arranged in an over-centred position. As a result, each tool can be made to be openable even if an unplanned stoppage should occur when the tool is positioned along said working path.

Each link mechanism may also comprise a roll which is held in a cam groove of the cam structure, a sensor being arranged in the cam groove for sensing the force by which the roll abuts against a bearing surface of the cam groove. This makes it possible to monitor the sealing force, i.e. the force by which the tool engages the material web, since this force is proportional to said abutting or contact force. The contact force of the roll can alternatively be sensed by means of a weakening in the cam groove, in which case the magnitude of the elastic deformation of the weakening is measured as the roll passes. Based on the magnitude of the elastic deformation, the force by which the roll abuts can easily be calculated.

According to another embodiment, the tool holder can be rotatably mounted on one side. The fact that the tool holder is mounted on one side only gives the advantage that the other side will be easy of access, which facilitates, for instance, service and tool changing.

According to one more embodiment, the device comprises a punching station, which is arranged downstream of the tool holder and arranged to punch container blanks along said connecting portions. The punching station can be arranged for such punching that a succession of container blanks are connected to each other to form a continuous web of container blanks.

In another embodiment, the device comprises a registering mechanism positioned upstream of the tool holder and adapted to sense the tension in the material web and to adjust said tension according to a predetermined value.

Furthermore, according to the present invention, a method is provided for producing container blanks from a material web by joining opposite wall portions of the material web along connecting portions, comprising

5 deflecting said material web over a tool holder, rotating the tool holder to move tools supported by the same along a working path, and, by continued rotation of the tool holder, moving the tools along a return path to the beginning of said working path, each tool, for pro-
10 viding said joining, being engaged with the material web and moved together with said material web during the movement of the tool along said working path.

According to one embodiment of the inventive method, the material web is folded to a web folded longitudinal-
15 ly in the form of a W.

According to yet another embodiment, each tool is engaged with the material web by pivoting an engaging element downwards to a base element for clamping the material web therebetween.

20 The tool holder is rotated continuously to provide continuous production of container blanks. The tool holder can also be rotated in an indexing motion.

Embodiments of the present invention will in the following be described for the purpose of exemplification
25 with reference to the accompanying drawings.

Brief Description of the Drawings

Fig. 1 is a schematic perspective view of an inventive device for producing container blanks.

30 Fig. 2 is a schematic side view of a control means for opening and closing of a tool supported by a tool holder of the inventive device, the control means being shown in a position corresponding to the open position of the tool.

35 Fig. 3 is a schematic side view of the control means in Fig. 2, the control means being shown in a position corresponding to the closed position of the tool.

Fig. 4 is a schematic side view of a tool of the inventive device in an open position.

Fig. 5 is a schematic side view of the tool in Fig. 4 in a closed position.

5

Description of Embodiments

Fig. 1, to which reference is made, illustrates schematically an embodiment of an inventive device 1 for producing container blanks 2 from a material web 3.

10 The device 1 is adapted to produce container blanks 2 by joining opposite wall portions of a material web 3. The material web 3 is obtainable in various designs. For example, it is possible to let the material web be a web folded longitudinally in the form of a W. A container
15 blank produced from such a material web will obtain two side walls from the outer lateral portions of the web and a bottom wall from the central portion, folded in two, of the web. It is also possible to produce such a container blank from a material web comprising two separate webs
20 and, arranged therebetween, a bottom forming web folded in two.

 The material web 3 from which said container blanks 2 are produced advantageously consists of a container laminate with a core layer comprising a binder of poly-
25 olefin and a filler of mineral material such as chalk.

 The device 1 comprises a rotatably arranged tool holder 4 which supports a number of tools 5. In the embodiment shown, the tool holder 4 has an octahedral structure where a tool 5 is arranged along the respective
30 sides of the structure. The tool holder 4 is supported by and rotatably mounted in a frame (not shown). In one embodiment (not shown) the tool holder can be rotatably mounted on one side. In such an embodiment, a mounting means is arranged on one side only of the tool holder,
35 which means that the opposite side of the tool holder is easily accessible, for instance, for service and tool changing.

By rotation of the tool holder 4, the tools 5 are movable along a path which comprises a working path and a return path, which are indicated at WP and RP.

Each tool 5 comprises a base element 6 and an engaging element 7. The base element 6 is fixedly mounted in the tool holder 4 and the engaging element 7 is pivotally arranged relative to the base element 6. For closing of the tool 5, the engaging element 7 is thus pivoted downwards into abutment against the base element 6.

The device 1 also comprises a control means (not shown in Fig. 1) for opening and closing of the tools 5. More specifically, the control means is arranged to close the tools 5 as they are being moved along said working path WP and open the tools 5 as they are being moved along said return path RP.

In operation of the device 1, a material web 3 is passed over a first deflecting roller 8 arranged upstream of the tool holder 4 and further over the base elements 6 of the tools 5 which are positioned along said working path WP. According to the embodiment shown, the material web 3 is then passed over a second deflecting roller 9 arranged downstream of the tool holder 4 and further to a subsequent station in the form of a punching station 10.

The tool holder 4 thus acts as a deflecting means for the material web 3.

When the material web 3 is fed towards the tool holder 4, it first reaches the beginning of the working path WP, said beginning being indicated in position A, and the tool 5 located in said position A is closed by the control means which thus provides downward pivoting of the engaging element 7.

As a result, the tool 5 will engage the material web 3, which engagement is maintained during rotation of the tool holder in the direction indicated by arrow P for moving the tool 5 to the end of the working path WP, which end is indicated in position B.

As the tool 5 moves from position A to position B, the tool 5 will thus be moved together with the material web 3 and engage the material web 3 for joining opposite wall portions along a connecting portion, which is indicated at 11.

At the same time the subsequent tool 5 will along the working path WP engage subsequent portions of the material web 3 for providing connecting portions 11 in the same way.

Once in position B, the control means is arranged to open the tool 5, and in the shown embodiment this is provided by pivoting the engaging element 7 upwards.

By continued rotation of the tool holder 5 in the direction of arrow P, the tool 5 will be moved along said return path RP back to the beginning of the working path WP, position A, where the tool 5 is again prepared to engage a portion of the material web 3.

The tools 5 can be arranged to provide said connecting portions 11 in different ways. In the embodiment shown, the engaging element 7 supports a rib 12 having an extent corresponding to a connecting portion 11, which rib 12 is arranged to engage the material web 3 to provide said connecting portion 11 in the container blank 2 by heat sealing. However, it will be appreciated that the rib 12 could also be supported by the base element 6, or that the base element 6 as well as the engaging element 7 support the rib 12.

The material web 3 is advantageously made of a laminate with an inside-forming surface layer having a melting point which is lower than the melting point of an outside-forming surface layer of the laminate. Thus by choosing a suitable sealing temperature and time, it will be possible to produce container blanks 2 from a web folded in the form of a W, or a web comprising two separate webs and, arranged therebetween, a web folded in two, without opposing outsides of the container blank 2 adhering to each other.

According to the present invention, container blanks 2 are thus produced by means of tools 5 which are kept substantially stationary in relation to a material web 3, whether this is stationary or continuously fed.

5 It is thus possible to let the inventive device 1 act as a deflecting means for a continuously fed material web 3, which for obvious reasons enables a higher production capacity since it would be possible to avoid intermittent operation. However, it will be appreciated
10 that the inventive device 1 can also be operated intermittently, if desired. For example, it is conceivable to arrange the tool holder 4 so as to be rotated in an indexing motion instead of being rotated continuously.

For the provision of uniform container blanks 2, it
15 is most important for the tension in the material web 3 to be kept substantially constant in operation. For this reason, the shown embodiment of the inventive device 1 comprises a registering mechanism 13, which is arranged downstream of the first deflecting roller 8.

20 In the embodiment shown, the registering mechanism 13 comprises a roll 14, over which the material web 3 runs and whose contact pressure against the material web 3 can be varied by an adjusting means 15, and a sensor (not shown) for measuring the tension in said material
25 web 3. The registering mechanism 13 is arranged to compare the value of the tension, detected by the sensor, with a predetermined value and after that adjust the contact pressure of the roll 14 by the adjusting means 15 so that it substantially corresponds to the predetermined
30 value.

Downstream of the tool holder 4, a punching station
10 is, as mentioned above, arranged to punch the completed container blanks 2 from the material web 3 along said connecting portions 11. In the shown embodiment, said
35 punching station 10 comprises a roll punch 16 which is arranged for such punching that two successive container blanks 2 are connected to each other to form a continuous

web 17 of container blanks 2. This web 17 of container blanks 2 can then be rolled up to be supplied in the form of rolls to the users.

For the necessary strength of the connecting portions 11, it is important for the sealing time to be sufficiently long. This means that each tool 5, at a given sealing temperature, must maintain its engagement with the material web 3 for a prescribed period of time, usually 1-2 s.

10 The inventive device 1 allows production of con-
tainer blanks 2 at a relatively high production capacity
and with reliable connecting portions 11.

The high production capacity is due to the fact that the device 1 allows continuous operation. More specifically, the tools 5 are moved by rotation of the tool holder 4, and by arranging the tools 5 at a suitable distance S from a centre of rotation C of the tool holder 4, the speed at which the tools 5 are moved can, at a given speed of rotation, be adjusted to the desired feed rate of the material web 3.

In spite of said high production rate, production of container blanks 2 with reliable connecting portions 11 is still allowed, which means that the resulting containers are liquid-tight in the filled state. By the tool holder 4 of the device 1 acting as a deflecting means for the material web 3, sufficiently long sealing times can in fact be achieved. The sealing time is at a given sealing temperature a function of speed and distance. Said distance is substantially the extent of said working path WP which is dependent on the one hand on how large part α of the revolution of the tool holder 4 is arranged as the working path WP and, on the other hand, the distance S of the tools 5 from the centre of rotation C of the tool holder 4. In the device 1 shown in Fig. 1, the working path WP corresponds approximately to half the revolution of the tool holder 4. Said speed is a function of said distance S to the centre of rotation C and the speed of

5

10

25

30

35

are held in a cam groove 24 of the cam structure 19. The second roll is rotatably fixed to the first roll. By rotation of the tool holder 4, the rolls 23, 29 of the holder 22 of the control means 18 will thus be moved
 5 along the cam groove 24, whereby the holder 25 is made to move along the bar 21 as a function of the profile of the cam groove 24.

The link mechanism 20 further comprises a first 25 and a second 26 link arm. A first end 27 of the first
 10 link arm 25 is articulated to the holder 22 and a second end 28 of said first link arm 25 is articulated to a first end 29 of the second link arm 26. A second end 30 of the second link arm 26 is finally fixedly connected to the engaging element 7 of the tool 5.

15 Fig. 2 shows the holder 22 of said link mechanism 20 in a lower end position, in which the tool 5 is open, i.e. the engaging element 7 is in its upwardly pivoted position relative to the base element 6 of the tool 5. The cam groove 24 of the cam structure 19 is thus formed
 20 with such a profile that the tool 5 is open when moved along the above-described return path RP.

When the tool 5 by rotation of the tool holder 4 has been moved to position A, i.e. to the beginning of the above-described working path WP, the control means 18 is
 25 arranged to close the tool 5, which thus means that the engaging element 7 is moved to its downwardly pivoted position relative to the base element 6. This is achieved according to the embodiment shown by moving the holder 22 of the link mechanism 20 to an upper end position, which
 30 is shown in Fig. 3 and thus means that said cam groove 24 has a profile for performing such a movement. Further the cam groove 24 is designed so that the tool 5 remains in its closed position when the tool 5 is moved along the working path WP to position B.

35 By the use of a cam structure 19 in combination with link mechanisms 20 which are connected to the respective tool 5, a control means 18 is provided, which in a reli-

5
10
15
20
25
30
35

5
10
15

20

25

30

35

engaging element 7 and the base element 6 comprise a projecting rib 12 of the type described above.

The engaging element 7 also comprises heating means (not shown), which are adapted to heat the rib 12 to
5 allow joining of the opposite wall portions along the desired connecting portion 11 by heat sealing.

The profile structure 33 is supported by a carrier structure 34 of the engaging element 7. In the embodiment shown, the profile structure 33 is provided with a number
10 of pins 35 on its side facing the carrier structure 34. The pins 35 extend through holes 36 formed in the carrier structure 34 and support stop washers 37 at their outer ends on the other side of the carrier structure 34.

Springs 38 are arranged around the pins 35 and positioned between the profile structure 33 and the carrier
15 structure 34. The springs 38 can be biased, in which case the magnitude of the bias is adjusted by the positioning of said stop washers 37.

The engaging element 7 is arranged in relation to
20 the base element 6 so that the springs 38, when the engaging means 7 has been moved to its downwardly pivoted position, are compressed to a predetermined extent. The force by which the profile structure 33 is applied to the back-pressure structure 32 thus depends on the current
25 spring constants and, possibly, the bias imparted to the springs 38. This arrangement of the pins 35 and springs 38 aims at providing a predetermined sealing force since the required sealing time is a function of temperature and precisely sealing force.

30 To provide satisfactory connecting portions 11, it is in some cases important for the sealing force to be optimally distributed along the entire rib 12. This can be provided by a suitable choice of bias or spring constant of the individual springs 38.

35 In accordance with that described above, it is important for a required sealing force to be provided during the engagement of the respective tools 5 with the

material web 3. It has also been described above how this sealing force is provided by an arrangement involving springs 38 which during the engagement of the tool 5 with material web 3 are compressed to a predetermined extent.

5 It will be appreciated that the required sealing force would be lost, for instance, if one of the springs 38 should break. In operation of the inventive device 1, this would in turn result in inferior quality of the connecting portions 11 which are provided by the tool 5 in

10 question, which could result in container blanks 2 that are not tight. According to an embodiment of the present invention, the device 1 comprises to this end a pressure sensor (not shown) which is arranged in the cam groove 24 of the cam structure 19 in that part of the groove 24

15 which corresponds to the working path WP of the tools 5. Each roll 23 of the respective link mechanisms 20 will then pass the sensor, whereby the contact force of the roll 23 against the pressure sensor is registered. This contact force is proportional to the sealing force, and

20 by comparing the current contact force with a predetermined value of said contact force it will thus be possible to discover inaccuracies, such as breakdown, in the arrangement involving springs 38. The contact force of the roll can also be read by means of a weakening in the

25 cam groove 24 of the cam structure 19, the magnitude of the elastic deformation of the weakening being measured as the roll 23 passes. The magnitude of the deformation is proportional to the contact force of the roll 23, which force can be measured without an additional part

30 having to be positioned in the cam groove.

In an embodiment (not shown) the profile structure is replaceable. The replaceability gives the advantage that different container forms can be produced by one and the same machine. One way of replaceably attaching the

35 profile structure is to use a modified keyhole lock. In the back of the profile structure, i.e. the side facing away from a container, a number of keyhole holes are

formed. By keyhole hole is meant a hole with which a pin can cooperate so that the pin can be inserted into the hole in a first direction and then be moved in a second direction to lock the pin from being moved in the first direction. On a frame, which is arranged to carry the profile structure, a number of pins are axially movably arranged, the location of the pins corresponding to the location of the keyhole holes. The pins are biased by means of springs pressing the profile structure against the frame when the pins are inserted into the keyhole holes. When the profile structure is to be replaced, a power source, such as a compressed-air source, is activated, said power source acting to move the pins in a direction opposite to said bias. The movement of the pins makes it possible to easily remove the profile structure, after which another profile structure can be mounted. Owing to the construction, considerable savings of time and labour can be achieved in service and exchange of the profile structures, compared with the case that each profile structure should be fastened by, for instance, screws.

According to the present invention, a device for producing container blanks from a material web thus is provided. The device comprises a rotary tool holder supporting tools, which are adapted to engage the material web and to be moved together with said material web along a working path under maintained engagement to join opposite wall portions of the material web along connecting portions. Moreover the tool holder acts as a deflecting means for the material web. As a result, a device is provided, which allows continuous production of container blanks at high production rates, although it is appreciated that the inventive device can also be operated intermittently.

It will be appreciated that the present invention is not limited to the shown embodiments.

5

Consequently several modifications and variations are conceivable, which means that the present invention is exclusively defined by the appended claims.